

FLOW SAFE EQUIPMENT CC

TEMPERATURE CONVERSION TABLE

1° to 40°			41° to 80°			81° to 290°		
C	C/F	F	C	C/F	F	C	C/F	F
-17.2	1	33.8	5	41	105.8	27.2	81	177.8
-16.7	2	35.6	5.6	42	107.6	27.8	82	179.6
-16.1	3	37.4	6.1	43	109.4	28.3	83	181.4
-15.6	4	39.2	6.7	44	111.2	28.9	84	183.2
-15.0	5	41	7.2	45	113	29.4	85	185
-14.4	6	42.8	7.8	46	114.8	30	86	186.8
-13.9	7	44.6	8.3	47	116.6	30.6	87	188.6
-13.3	8	46.4	8.9	48	118.4	31.1	88	190.4
-12.8	9	48.2	9.4	49	120.2	31.7	89	192.2
-12.2	10	50.0	10.0	50	122	32.2	90	194
-11.7	11	51.8	10.6	51	123.8	32.8	91	195.8
-11.1	12	53.6	11.1	52	125.6	33.3	92	197.6
-10.6	13	55.4	11.7	53	127.4	33.9	93	199.4
-10.0	14	57.2	12.2	54	129.2	34.4	94	201.1
-9.4	15	59.0	12.8	55	131	35	95	203
-8.9	16	60.8	13.3	56	132.8	35.6	96	204.8
-8.3	17	62.6	13.9	57	134.6	36.1	97	206.6
-7.8	18	64.4	14.4	58	136.4	36.7	98	208.4
-7.2	19	66.2	15	59	138.2	37.2	99	210.2
-6.7	20	68.0	15.6	60	140	37.8	100	212
-6.1	21	69.8	16.1	61	141.8	43	110	230
-5.6	22	71.6	16.7	62	143.6	49	120	248
-5.0	23	73.4	17.2	63	145.4	54	130	266
-4.4	24	75.2	17.8	64	147.2	60	140	284
-3.9	25	77.0	18.3	65	149	66	150	302
-3.3	26	78.8	18.9	66	150.8	71	160	320
-2.8	27	80.6	19.4	67	152.6	77	170	338
-2.2	28	82.4	20	68	154.4	82	180	356
-1.7	29	84.2	20.6	69	156.2	88	190	374
-1.1	30	86.0	21.1	70	148	93	200	392
-0.6	31	87.8	21.7	71	159.8	99	210	410
0.0	32	89.6	22.2	72	161.6	100	212	413.6
0.6	33	91.4	22.8	73	163.4	104	220	428
1.1	34	93.2	23.3	74	165.2	110	230	446
1.7	35	95.0	23.9	75	167	116	240	464
2.2	36	96.8	24.4	76	168.8	121	250	482
2.8	37	98.6	25	77	170.6	127	260	500
3.3	38	100.4	25.6	78	172.4	132	270	518
3.9	39	102.2	26.1	79	174.2	138	280	536
4.4	40	104.0	26.7	80	176	143	290	554

Locate temperature in middle column. If in Deg C, read F equivalent in right hand column. If in Deg F read C equivalent in left hand column.

This table is meant as a GUIDE ONLY